



Renewable Lubricants, Inc.

476 Griggy Rd., P.O. Box 474

Hartville, Ohio 44632-0474

Voice: 330.877.9982 Fax 330.877.2266

Web: www.renewablelube.com

Bio-Dry Slide™ Lubricant Food Grade H1 (Anti-wear, Anti-stick Release Agent)



"Biobased Lubricants that Perform Like Synthetics"

Bio-Dry Slide Lubricant is a biobased Extreme Pressure (EP) formulation specially designed for lubricating sliding surfaces that require a fast dry solid lubricant or release agent. This product is fortified with a food grade¹ synthetic white graphite EP that lubricates and reduces friction equal or better than PTFE. It is formulated in a unique **biodegradable**, biobased carrier and provides excellent Coefficient of Friction (0.08) on sliding surfaces with added anti-rust, anti-oxidation, and anti-wear protection. In addition, this white graphite has shown to provide improved lubrication over 1000°C after black graphite, PTFE, and molybdenum disulfide loses their lubrication between 400°C and 500°C. It contains no Trichloroethylene, Perchloroethylene, Tetrafluoroethane, heavy metals, lead, antimony, zinc, or chlorine.

Bio-Dry Slide Lubricant is an ENVIRONMENTALLY RESPONSIBLE product that is formulated from renewable agricultural plant resources. We believe Earth's environmental future rests in the use of renewable materials.

Application: Shake Well Before Use

Bio-Dry Slide Lubricant provides anti-stick in molds, fixtures, dies, and assembly machines. It is specifically designed not to leave an oily film that will attract dirt and provide anti-wear protection in sliding surfaces. It will provide a white lubricating solid film after the biobase carrier cleanly dissipates. Other applications including: pipe threads, bolts, hinges, tool, drive chains, guns, bicycle chains, wire ropes, cables, slide-ways, and heavy hinge pins. The perfect solution for sticking or squeaking doors, windows, drawers, locks, zippers, moving machinery parts, skates, bikes, sleds, skis, reels. It penetrates around moving parts and leaves a white dry lubrication film to prevent rust and corrosion. It's an extreme pressure lubricant that's an excellent treatment for leaf springs, steering and suspension components, battery connections and any other metal surfaces that are subject to rust and corrosion.

Typical Specifications:

Color	White
Texture	Fast Dry Solid Powder
Solvent Carrier	Biobased Volatile Liquid
Viscosity @40°C, cSt. (D-445)	6 cSt
Flash Point (PMCC) ASTM D-93	(Flammable) 12.7°C
Pour Point ASTM D-97	-114 C°
Corrosion Test ASTM D-665	Pass Clean
Copper Corrosion ASTM D-130	1A
4-Ball Wear ASTM D-2266	0.4 mm
4-Ball EP ASTM D-2596	Weld 200 kg

¹Food Grade components in this product are listed in 21 CFR 178.3570, Lubricants for incidental food contact (USDA HX-1 for use in H1). Full compliance with other applicable restrictions of FDA, USDA, oil spill, and oil pollution prevention statutes is recommended.

STABILIZED by Renewable Lubricants* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

* Trademark of Renewable Lubricants, Inc.
Copyright 1999 Renewable Lubricants, Inc.

Availability	F.O.B. :Manufacturer	12oz. Spray	1 Gallon
Product Item #		81990	81993