



Renewable Lubricants™, Inc.

476 Griggy Rd., P.O. Box 474

Hartville, Ohio 44632-0474

Voice: 330.877.9982 Fax 330.877.2266

Web: www.renewablelube.com

Bio-Food Grade™ FR
Hydraulic Fluid
(ISO 32, 46, & 68)



"Biobased Lubricants that Perform Like Synthetics"

Bio-Food Grade™ FR Hydraulic Fluids are fire resistant (FR) biobased lubricants that contain ingredients, which are “Generally Regarded as Safe” (GRAS) for food processing equipment. These food grade¹ hydraulic fluids are ultimate biodegradable and environmentally non-toxic and can be used in environmentally sensitive areas such as in agriculture, marine, water treatment, and food processing plants. They are **Specially formulated to offer the lowest toxicity in aquatic conditions** to meet and exceed the requirements of International Ecolabels and US Environmental Protection Agency (EPA) Vessel General Permit (VGP) guidelines for EALs. In addition, the products exceed the USDA Biobased new carbon at >90%. They are an excellent choice for inner plant applications (ie. Steel Mills) as fire resistant hydraulic fluids and they provide exceptional oxidation stability (RPVOT avg. 250 minutes) exceeding US Steel minimum requirement of 120 minutes. **Although they have a pour point of -30°C to -35°C, care must be taken if used in hydraulic systems setting static below -15°C for extended periods.** Contains no animal byproducts and are manufactured under kosher supervision.

Bio-Food Grade™ FR Hydraulic Fluids are formulated to perform in stationary and mobile hydraulic systems that require Anti-Wear, Anti-Rust and Anti-Oxidation properties. These patented super high VI fluids have a long history of successfully being used in hydraulic systems designed with vane, piston, and gear-type pumps, that require DIN 51524 Part 2 and 3, Parker-Denison HF-O, HF-1, HF-2, Eaton-Vickers, Rexroth, and Sauer-Sundstrand. They have shown to have exceptional anti-wear performance in ASTM D-4172 Four Ball Wear Tests. Their anti-wear performance **exceeds the requirements** for US Steel 126, 136 and 127, DIN 51524 Part 2 and 3 load stage 10 in the FZG (DIN 51354). They also meet and exceed the requirements for ashless GL-1, GL-2, GL-3 and AGMA Non-EP gear oils in reduction units and gear sets where they meet the viscosity ranges. They are highly inhibited against moisture and rusting in both fresh and sea water and pass A and B Sequences of the ASTM D-665 Turbine Oil Rust Test. Incorporating the super high viscosity index of the Stabilized* High Oleic Base Stocks (HOBS) into the formulas, gives multi-grade synthetic base oils performance by boosting the viscosity index to synthetic levels (Energy Conserving Formulas). An environmentally friendly, zinc-free additive system has also been developed that meets or exceeds high pressure pump requirements.

Fire Resistant Performance: The super high viscosity index of the HOBS naturally improves the thermal shear stability of the formulas and load capacity. The HOBS’s extremely low volatility (NOACK <1) and excellent oxidation stability improves the flash and fire safety features in these formulas. In ASTM D-92, Flash Points range from 518°F (270°C) to 545°F (285°C) and Fire Points range from 610°F (321°C) to 635°F (335°C). Based on previous test results, Bio-Food Grade™ FR Hydraulic Fluids ISO 32, ISO 46, and ISO 68 can be Factory Mutual approved as less hazardous fluid “Specification Tested” ISO/CD 15029-3 rating (HFDU), and ISO/TS 15029-2 Spray Ignition-Ignitability (Class H). The tests have supported the expected temperature ranges of Autoignition (ASTM D-2155) @ 752 - 815°F (400 - 435°C) and Manifold Ignition (ISO 20823) @ 824 - 896°F (440 - 480°C).

- Meet the Environmental Protection Agency (EPA) 2013 Vessel General Permit (VGP) guidelines for ENVIRONMENTALLY ACCEPTED LUBRICANTS (EALs), and should be used where LOW TOXICITY, BIODEGRADABILITY and NON-BIOACCUMULATION properties are required.
- They exceed the acute toxicity (LC-50 / EC-50 >1000 ppm) criteria adopted by the US Fish and Wildlife Service and the US EPA.
- They are ENVIRONMENTALLY RESPONSIBLE lubricants formulated from renewable agricultural biobased resources.
- Earth's environmental future rests in the use of renewable materials.

¹Food Grade components in this product are listed in 21 CFR 178.3570, Lubricants for incidental food contact (USDA HX-1, H1). Full compliance with other applicable restrictions of FDA, USDA, oil spill, and oil pollution prevention statutes is recommended.

STABILIZED by Renewable Lubricants* is RLI’s trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

Patented Product with Pending and Foreign Patents Copyright 1999 Renewable Lubricants, Inc.
 ™Trademark of Renewable Lubricants, Inc.

Bio-Food Grade™ FR Hydraulic Fluids

TYPICAL SPECIFICATIONS TEST	METHOD	<u>ISO 32</u>	<u>ISO 46</u>	<u>ISO 68</u>
Viscosity @ 40°C	ASTM D-445	34.5	46.1	64.5
Viscosity @ 100°C	ASTM D-445	7.6	9.75	12.8
Viscosity @ -15°C, Brookfield	ASTM D-2983	17,000 cP	20,000 cP	24,000 cP

Viscosity Index	ASTM D-2270	199	204	202
Pour Point	ASTM D-97	-35°C	-32°C	-30°C
Flash Point (COC)	ASTM D-92	270°C	280°C	285°C
Fire Point (COC)	ASTM D-92	321°C	330°C	335°C
NOACK Volatility 1 hr @ 250°C	DIN51581	<2%	<1%	<1%
Foam Sequence I, II, III (10 min)	ASTM D-892	20/0	20/0	20/0
Rust Prevention	ASTM D-665	Pass/Clean	Pass/Clean	Pass/Clean
Distilled Water		Pass/Clean	Pass/Clean	Pass/Clean
Syn. Sea Water		Pass/Clean	Pass/Clean	Pass/Clean
Accelerated Storage Stability		Pass	Pass	Pass
Copper Corrosion Strip 3hr @ 100°C	ASTM D-130	1A	1A	1A
RPVOT, (min)	ASTM D-2272	250	250	250
Dielectric Strength, KV (Avg)	ASTM D-877	47	47	46
Acid Number	ASTM D-974	1.1	1.1	1.1
Elastomer Testing BUNA-N Rubber				
Volume Change, %	D-471	8.0	2.0	2.0
Shore A Hardness Change	D-2240	-6	0.0	0.0
Demulsibility, ML Oil/Water/Emulsion	ASTM D-1401	40/ 40/ 0	40/ 40/ 0	40/ 40/ 0
4-Ball Wear, 1h, 167°F, 1200 RPM, 40 kg	ASTM D-4172	.30-.40	.30-.40	.30-.40
FZG Test A/8,3/90	DIN 51354 Part 2	12	12	12
Biodegradability	CEC-L33-T-82	>80%	>80%	>80%
	OECD 301B Mod. Sturm	>60%	>60%	>60%
	ASTM D-5864	>60%	>60%	>60%
Ecotoxicity				
Fathead minnow, 96h LC50, ppm		>10,000 ppm	>10,000 ppm	>10,000 ppm
Daphnis magna, 48 h, EC50, ppm		>10,000 WAF	>10,000 WAF	>10,000 WAF
Sludge respiration inhibition, EC50, ppm		>10,000 ppm	>10,000 ppm	>10,000 ppm
Meets EPA requirements 560/6-82-002, 560/6-82-003		Yes	Yes	Yes
Biodegradation Classification	ASTM D-5864	Ultimate PW1	Ultimate PW1	Ultimate PW1
Environmentally Friendly	ISO 15380	Yes	Yes	Yes
USDA BioPreferredSM	New Carbon	yes	yes	yes
Environmental Management System	ISO 14001:1996	yes	yes	yes
RLI Product	Item #	88510	88520	88530

Availability F.O.B.: Hartville, Ohio, USA 1 Gallon 5 Gallon Pail Drum Totes Bulk

