



## Renewable Lubricants, Inc.

476 Griggy Rd., P.O. Box 474  
 Hartville, Ohio 44632-0474  
 330.877.9982 Fax 330.877.2266  
 Web: www.renewablelube.com

### Bio-SynXtra™ 80W140 GL-5 Gear Lubricant



### *"Biobased Lubricants that Perform Like Synthetics"*

Bio-SynXtra™ 80W140 GL-5 is designed to meet/exceed the SAE J306 and SAE J2360 requirements for heavy transmissions, differentials, and transfer cases. Increasing the additive technology above GL-5 provides additional performance and Extreme Pressure (EP) protection for spiral bevel, worm, and hypoid gears. This biobased formula has combined Stabilized HOBS technology with synthetic base stocks to provide a super high viscosity index (VI) with fuel savings performance. The result is an inherently biodegradable product which has the long life heat stability but which additionally offers the protection advantages of increased gear life through extremely high film strength and excellent low temperature performance. This product may be used for top-off of differentials and is compatible with hydrocarbon and synthetic PAO based gear oils. Bio-SynXtra™ 80W140 GL-5 Gear Lubricant is an ENVIROMENTALLY RESPONSIBLE lubricant that is formulated from renewable agricultural resources. We believe Earth's environmental future rests in the use of renewable material.

#### Typical Specifications

SAE Gear Grade	80W140
Specific Gravity @60°F (D-287)	0.90
VISCOSITIES:	
@100°C., cSt. (D-445)	26
@40°C., cSt. (D-445)	164
Viscosity Index (D-2270)	194
Viscosity, Brookfield cP @ -26 °C	77,000
Flash Point, COC, °C (D-92)	252
Pour Point, °C (D-97)	-36
Copper Corrosion Strip 3hr @ 100°C (D-130)	1B
4 Ball Wear, 1h, 167°F, 1200 RPM, 40kg (D-4172)	.30
Demulsibility (D-2711)	Pass
Foam Sequence I, II, III (D-892)	Pass
Rust Prevention (D-665 A&B)	Pass

- Features**
- (1) Recommended for API Service Classifications GL-4, GL-5, and GL-6
  - (2) Super high viscosity index and low pour point for wide temperature usage
  - (3) Fortified with additional additives to resist wear, oxidation, rust and foam
  - (4) Exceeds U.S. Steel and AGMA antiwear and EP performance for industrial gear applications
  - (5) Excellent low temperature channeling and demulsibility properties
  - (6) Biodegradable and Energy Conserving

STABILIZED by Renewable Lubricants\* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

Patented Product: US Patent 6,383,992, US Patent 6,534,454 with additional Pending and Foreign Patents

\* Trademark of Renewable Lubricants, Inc.  
 Copyright 1999 Renewable Lubricants, Inc.

<u>Availability</u>	<u>F.O.B. :Hartville, Ohio, USA</u>	<u>Quart</u>	<u>1 Gallon</u>	<u>5 Gallon Pail</u>	<u>Drum</u>	<u>Totes</u>	<u>Bulk</u>
Item #		82151	82153	82154	82156	82157	82159