



## Renewable Lubricants, Inc.

476 Griggy Rd., P.O. Box 474  
Hartville, Ohio 44632-0474  
330.877.9982 Fax 330.877.2266  
Web: www.renewablelube.com

### **Bio-Process™ Oils (SUS-50, 70, 100, 150, 200)**

(Food Grade H1)

**STABILIZED™**  
by Renewable Lubricants

### *"Biobased Lubricants that Perform Like Synthetics"*

Bio-Process™ Oils are blended highly refined Biosynthetic base oils (Biobased) that replace neutral petroleum mineral oils in industrial processing applications. They have been Stabilized\* to resist oxidation and provide excellent light color stability. They are virtually aromatic, chlorine, and sulfur free and may be used in dust control as a dust suppressant. The oils have been highly refined, bleached, deodorized and are high in oleic acid content for higher stability over conventional vegetable oils. In addition, they provide excellent compatibility with elastomers, mineral and synthetic oils, and provide excellent lubricity for recommended applications.

Bio-Process™ Oils are non-toxic, Food Grade<sup>2</sup>, and exceeds U.S. FDA regulation 21 CFR 178.3620 (b and c), for use as canning oils, dust suppressants, paper defoamers, in adhesives, rubber articles, and as a surface lubricant in the food packaging area and canning facilities. They are ideal for use in compounding asphalt and a wide variety of finished rubber products where certain performance is desired in formulas. They also function as processing aid in, and extender oils in rubber compounding where vegetable oils may enhance the process. Bio-Process™ Oils are named for their approximate Saybolt viscosity, in SUS at 100°F.

Bio-Process™ Oils are ENVIRONMENTALLY RESPONSIBLE base oils that are formulated from renewable agricultural plant resources. We believe Earth's environmental future rests in the use of renewable material.

The advantages are many: biodegradable<sup>1</sup>, renewable, low toxicity, no volatile organic compounds (VOCs), safer, more fire resistant, EPA and ISO 14000 compliant, reduces foreign oil, and helps secure the American Economy. OSHA and worker acceptance is high with biobased oils.

#### **Typical Specifications**

Viscosity Grade (SUS)	50	70	100	150	200
Viscosity, cSt @40°C (D-445)	7.3	13.0	20.9	31.7	38.0
API Gravity @ 60°F. (D-287)	36.8	32.6	29.3	26.7	25.6
Pounds/Gallon @ 60°F.	7.08	7.18	7.32	7.45	7.50
Spec. Gravity @ 60°F.(D-287)	0.85	0.87	0.88	0.89	0.90
Flash Point, COC, °C (D-92)	146	180	220	250	290
Pour Point, °C (D-97)	-20	-20	-20	-20	-20
*Stabilized-Oxidation Inhibited RLI Product Item #	Yes 87020	Yes 87030	Yes 87040	Yes 87050	Yes 87060

STABILIZED by Renewable Lubricants\* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

<sup>1</sup> Ultimate Biodegradation (Pw1) within 28 days in ASTM D-5864 Aerobic Aquatic Biodegradation of Lubricants

<sup>2</sup> Base oils and additives in this product are listed in 21 CFR 178.3570, Lubricants for incidental food contact (USDA H1). Full compliance with other applicable restrictions of FDA, USDA, oil spill, and oil pollution prevention statutes is recommended.

Patented Product: US Patent 6,383,992, US Patent 6,534,454, US Patent 6,624,124, US Patent 6,620,772 with additional Pending and Foreign Patents

\* Trademark of Renewable Lubricants, Inc. Copyright 1999 Renewable Lubricants, Inc.

**Availability F.O.B. :Hartville, Ohio, USA 1 Gallon 5 Gallon Pail Drum Totes Bulk**