# SAFETY DATA SHEET

Version 1 Issue Date: 15 May 2015 Revision date: 15 May 2015

# 1. - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

**Product Name: Bio-Metal Cool GP** (Water Emulsifiable Metal Working Fluid)

Other means of identification

Product code: 86801, 86803, 86804, 86806

CAS NO: Mixture **Synonyms:** None

Recommended use of the chemical and restrictions on use

**Recommended Use:** Biobased Water Emulsifiable Cutting Fluid for Metal Working

# Details of the supplier of the safety data sheet

# **Supplier and Manufacture**

Renewable Lubricants, Inc. 476 Griggy RD NE, P.O. Box 474

Hartville, Oh 44632 Phone: (330) 877-9982 Fax: (330) 877-2266

www.renewablelube.com, www.renewablelubricants.com

### 2. Hazard(s) identification

#### **Hazard Classification**

### **Health Hazards**

Serious Eye Damage/Eye Category 2B Irritation

# **Unknown toxicity**

0.0 % Acute toxicity, oral Acute toxicity, dermal 0.0 % Acute toxicity, inhalation, vapor 56 % Acute toxicity, inhalation, dust 55 %

or mist

### Label Elements:

**Hazard Symbol:** No symbol

Signal Word: Warning

**Hazard Statement:** Causes eye irritation.

**Precautionary Statement:** 

Prevention: Wash thoroughly after handling.

Response: If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Material Name Bio-Metal Cool GP Page 1 of 11 Issue Date: 15 May 2015

1/11

**Disposal:** Dispose of contents/container to an appropriate treatment and

disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result

None identified.

in GHS classification:

# 3. Composition/information on ingredients

Chemical name	CAS number	Percent by Weight
Mineral oil	64742-54-7	30 - 40%
Biobased ester mixture	Not determined.	50 - 60%
Hexylene glycol	107-41-5	0.5 - 1%

The mineral oil contained in this material may be described by one or more of the following CAS Nos.: 64742-54-7, 64742-65-0, 64742-55-8, and 64742-56-9.

**Trade secret information:** A specific chemical identity and/or percentage of composition has been

withheld as a trade secret.

4. First-aid measures

**Ingestion:** Treat symptomatically. Get medical attention.

**Inhalation:** Remove exposed person to fresh air if adverse effects are observed.

**Skin Contact:** Wash with soap and water. Get medical attention if symptoms occur.

Launder contaminated clothing before reuse.

**Eye contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** See section 11.

Indication of immediate medical attention and special treatment needed

**Treatment:** Treat symptomatically.

5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing CO2, I

media:

CO2, Dry chemical or Foam. Water can be used to cool and protect

exposed material.

Unsuitable extinguishing

media:

Not determined.

Specific hazards arising from

See section 10 for additional information.

the chemical:

Special protective equipment and precautions for firefighters

Material Name Bio-Metal Cool GP Page 2 of 11 Issue Date: 15 May 2015

2/11

Special fire fighting procedures:

No data available.

Special protective equipment for fire-fighters:

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants,

gloves and boots.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Personal Protective Equipment must be worn, see Personal Protection

Section for PPE recommendations.

Methods and material for containment and cleaning up:

Dike far ahead of larger spill for later recovery and disposal. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Stop the flow of material, if this is without risk. Prevent entry into

waterways, sewer, basements or confined areas.

**Environmental Precautions:** Avoid release to the environment. Do not contaminate water sources or

sewer. Prevent further leakage or spillage if safe to do so.

# 7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Observe good industrial hygiene practices.

> Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid environmental

contamination.

**Maximum Handling** 

Temperature:

60 °C 140 °F

Conditions for safe storage,

including any incompatibilities: Store away from incompatible materials. See section 10 for incompatible

materials.

**Maximum Storage** Temperature:

45 ℃ 113 ℉

# 8. Exposure controls/personal protection

#### **Control Parameters:**

# **Occupational Exposure Limits**

Chemical name	type	Exposure Limit Values		Source
Mineral oil - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Mineral oil - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (02 2012)
Mineral oil - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
Mineral oil - Mist.	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
Mineral oil - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hexylene glycol	Ceiling	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Hexylene glycol	Ceiling	25 ppm		US. ACGIH Threshold Limit Values (02 2012)
Hexylene glycol	Ceil_Time	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)

Appropriate engineering

controls:

Mechanical ventilation or local exhaust ventilation may be required. Use material in well ventilated area only. No special requirements under

ordinary conditions of use and with adequate ventilation.

Individual protection measures, such as personal protective equipment

**General information:** Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists,

mechanical generation of dusts, drying of solids, etc.

**Eye/face protection:** Safety glasses. If potential for splash or mist exists, wear chemical goggles

or faceshield.

**Skin Protection** 

**Hand Protection:** Use nitrile or neoprene gloves. Use good industrial hygiene practices. In

case of skin contact, wash hands and arms with soap and water.

Other: No data available.

**Respiratory Protection:** Use respirator with a combination organic vapor and dust/mist cartridge.

Use respirator if irritation is experienced or if the recommended exposure limit is exceeded. A respiratory protection program compliant with all applicable regulations must be followed whenever workplace conditions require the use of a respirator. Under normal use conditions, respirator is not usually required. Use appropriate respiratory protection if exposure to dust particles, mist or vapors is likely. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas

and for large spill clean-up sites.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing to remove contaminants. Discard contaminated

footwear that cannot be cleaned.

# 9. Physical and chemical properties

**Appearance** 

Physical state:liquidForm:liquidColor:DarkOdor:Pungent

Odor threshold: No data available.

**pH**: < 10

Freezing point:

Boiling Point:

No data available.

No data available.

Flash Point:  $> 464 \, ^{\circ}\text{F} (240 \, ^{\circ}\text{C}) (COC)$ 

**Evaporation rate:**No data available. **Flammability (solid, gas):**No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

Material Name Bio-Metal Cool GP Page 4 of 11

Issue Date: 15 May 2015 4/11

Vapor pressure:No data available.Vapor density:No data available.

**Relative density:** 0.91 - .92 60.1 °F (15.6 °C)

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
Decomposition temperature:
No data available.
Viscosity:
68 cSt @ 40°C

Other information

**Bulk density:** 7.6 lb/gal 77 °F (25 °C)

Pour Point Temperature: 10 °F (-12 °C)

# 10. Stability and reactivity

**Reactivity:** Not applicable.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

Will not occur.

**Conditions to avoid:**Do not expose to excessive heat, ignition sources, or oxidizing materials.

**Incompatible Materials:** Strong oxidizing agents.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may generate smoke, carbon monoxide, carbon dioxide, nitrogen oxides, and other products of

incomplete combustion. Thermal decompositon may generate potassium

oxides and other potassium containing compounds.

### 11. Toxicological information

# Information on likely routes of exposure

**Inhalation:** No data available.

**Ingestion:** No data available.

**Skin Contact:** No data available.

**Eye contact:** Causes eye irritation.

# Information on toxicological effects

**Acute toxicity** 

Oral

Product: Ingestion can cause central nervous system effects such as

headache, dizziness, drowsiness, and generalized weakness.

ATEmix > 10,000 mg/kg.

Dermal

Product: Prolonged or widespread contact with this material could result in

the absorption of potentially harmful amounts.

Not classified for acute toxicity based on available data.

Material Name Bio-Metal Cool GP Page 5 of 11 Issue Date: 15 May 2015

Inhalation

Product: Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product: Classification: Not irritating (Read across); Rabbit.

Remarks: Prolonged or repeated skin contact as from clothing wet

with material may cause dermatitis. Symptoms may include

redness, edema, drying, and cracking of the skin.

Not classified as a primary skin irritant.

Serious Eye Damage/Eye Irritation:

Product: Classification: Slightly irritating. (Read across); Rabbit.

Remarks: Causes eye irritation.

Respiratory sensitization:

No data available

Skin sensitization:

Product: Remarks: Risk of sensitization or allergic reactions among sensitive

individuals.

Mineral oil Classification: Not a skin sensitizer. (Read across)

Mineral oil Classification: Not a skin sensitizer. (Read across)

Hexylene glycol Remarks: This product contains hexylene glycol which has been

reported to cause dermatitis in sensitive individuals.

**Specific Target Organ Toxicity - Single Exposure:** 

Product: If material is misted or if vapors are generated from heating,

exposure may cause irritation of mucous membranes and the upper

respiratory tract.

Mineral oil If material is misted or if vapors are generated from heating,

exposure may cause irritation of mucous membranes and the upper

respiratory tract.

Hexylene glycol May cause irritation to the mucous membranes and upper

respiratory tract.

**Aspiration Hazard:** 

Mineral oil Material can be aspirated into the lungs during the act of swallowing

or vomiting. This could result in severe injury to the lungs and death.

**Chronic Effects** 

Carcinogenicity:

Product: This product contains mineral oils which are severely refined and not

considered carcinogenic. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346

test.

15 May 2015 6/11

Mineral oil All of the oils in this product have been demonstrated to contain less

than 3% extractables by the IP 346 test. This product contains mineral oils which are severely refined and not considered

carcinogenic.

### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

# US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

#### **Germ Cell Mutagenicity:**

Product: Not expected to be a germ cell mutagen, based on assessment of the components.

### Reproductive toxicity:

Product: Not expected to be a reproductive toxicant, based on assessment of the components

### **Specific Target Organ Toxicity - Repeated Exposure:**

Product: Not expected to cause organ damage from repeated exposure.

# 12. Ecological information

### **Ecotoxicity**

Fish

Mineral oil LC 50 (Fathead Minnow, 4 d): > 100 mg/l
Hexylene glycol LC 50 (Fathead Minnow, 4 d): > 5,000 mg/l
Biobased ester mixture LC 50 (Fathead Minnow, 4 d): > 5,000 mg/l

**Aquatic Invertebrates** 

Mineral oil EC 50 (Water flea (Daphnia magna), 2 d): > 10,000 mg/l

EC 50 (Water flea (Daphnia magna), 21 d): > 10 mg/l NOEC (Water flea (Daphnia magna), 21 d): 10 mg/l

Biobased ester mixture EC 50 (Water flea (Daphnia magna), 2 d): > 10,000 mg/l

EC 50 (Water flea (Daphnia magna), 21 d): > 10 mg/l NOEC (Water flea (Daphnia magna), 21 d): > 10 mg/l

7/11

Hexylene glycol EC 50 (Water flea (Daphnia magna), 2 d): > 2,000 mg/l

**Toxicity to Aquatic Plants** 

Mineral oil EC 50 (Green algae (Scenedesmus quadricauda), 3 Days): > 100

mg/l

Biobased ester mixture EC 50 (Green algae (Scenedesmus quadricauda), 3 Days): > 1000

ma/l

### Toxicity to soil dwelling organisms

No data available

Material Name Bio-Metal Cool GP Page 7 of 11 Issue Date: 15 May 2015 **Sediment Toxicity** 

No data available

**Toxicity to Terrestrial Plants** 

No data available

**Toxicity to Above-Ground Organisms** 

No data available

Toxicity to microorganisms

Hexylene glycol EC 50 (Bacteria, 0.1 d): > 100 mg/l

**Persistence and Degradability** 

Biodegradation

Mineral oil OECD TG 301 B, 31 %, 28 d, Inherently biodegradable.

Hexylene glycol Miscellaneous, 95 %, 28 d, Readily biodegradable

Biobased ester mixture OECD TG 301 B, > 60 %, 28 d, Readily biodegradable

**Bioaccumulative Potential** 

**Bioconcentration Factor (BCF)** 

Product Expected to be biodegradable

Partition Coefficient n-octanol / water (log Kow)

Hexylene glycol Log Kow: 0.58 (Measured)

**Mobility:** 

No data available

Other Adverse Effects: No data available.

13. Disposal considerations

**Disposal instructions:** Treatment, storage, transportation, and disposal must be in accordance

with applicable Federal, State/Provincial, and Local regulations.

Dispose of packaging or containers in accordance with local, regional, national and international regulations. Empty container contains product

residue which may exhibit hazards of product.

**Contaminated Packaging:** Container packaging may exhibit hazards.

# 14. Transport information

DOT

Not regulated.

Not regulated.

Not regulated.

Material Name Bio-Metal Cool GP Page 8 of 11 Issue Date: 15 May 2015

# Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

None known.

The DOT shipping information in this section is based on a bulk container. Please review the accompanying shipping papers for the correct shipping descriptions based the size of the package. Shipping descriptions may vary based on mode of transport, quantities, temperature of the material, package size, and/or origin and destination. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. During transportation, steps must be taken to prevent load shifting or materials falling, and all relating legal statutes should be obeyed. Review classification requirements before shipping materials at elevated temperatures.

# 15. Regulatory information

# **US Federal Regulations**

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

### **CERCLA Hazardous Substance List (40 CFR 302.4)**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 311/312 Classifications

(Acute) Health Hazards

#### **SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

#### SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

# SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

### **US State Regulations**

### **US. California Proposition 65**

None present or none present in regulated quantities.

# **Inventory Status**

Australia (AICS)

All components are in compliance with chemical notification requirements in Australia.

### Canada (DSL/NDSL)

All components are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substances List.

# China (IECSC)

All components of this product are listed on the Inventory of Existing Chemical Substances in China.

#### European Union

All components are in compliance with the EC Seventh amendment Directive 92 /32/EEC.

#### Japan (ENCS)

All components are in compliance with the Chemical Substances Control Law of Japan.

#### Korea (ECL)

All components are in compliance in Korea.

#### New Zealand (NZIoC)

This product requires notification before sale in New Zealand.

#### Philippines (PICCS)

All components are in compliance with the Philippines Toxic Substances and Hazardous and Nuclear Wastes Control Act of 1990 (R.A. 6969).

#### Switzerland (SWISS)

All components are in compliance with the Environmentally Hazardous Substances Ordinance in Switzerland.

### Taiwan (TCSCA)

All components of this product are listed on the Taiwan inventory.


#### United States (TSCA)

All components of this material are on the US TSCA Inventory.

The information that was used to confirm the compliance status of this product may deviate from the chemical information shown in Section 3.


# 16.Other information, including date of preparation or last revision

#### **HMIS Hazard ID**



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; \*Chronic health effect

### **NFPA Hazard ID**



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible

**Issue Date:** 02/19/2016

Version #: 2.0

**Source of information:** Internal company data and other publically available resources.

**Further Information:** Contact supplier (see Section 1)

Disclaimer:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user.

Material Name Bio-Metal Cool GP Page 11 of 11 Issue Date: 15 May 2015