



Renewable Lubricants, Inc.

476 Griggy Rd., P.O. Box 474
 Hartville, Ohio 44632-0474
 Voice: 330.877.9982 Fax 330.877.2266
 Web: www.renewablelube.com



Bio-SynXtra™ Marine 2 Cycle Engine Oil

(High performance Universal Water and Air cooled 2 cycle engine oil)

"Biobased Lubricants that Perform Like Synthetics"

Bio-SynXtra™ Marine 2 Cycle Engine Oil is a patented, readily biodegradable¹, biobased synthetic formula, that meets and exceeds the EPA-VGP, National Marine Manufacturers Association (NMMA) requirements for TC-W3™ Water-Cooled 2T Outboard Engines, and API TC+ for high performance air cooled engines. It replaces NMMA obsolete Water-Cooled TC-W (BIA), TC-WII for older outboard water-cooled engines, and NMMA TC-W3™ newer outboard water-cooled engines requirements. This high performance 2-Cycle formula provides additional antiwear/anti-scuffing protection and is recommended for use in lawn and garden equipment, chain saws, snow blowers, motor scooters, mopeds, snowmobiles and outboard water-cooled engines. **TC-W3™ is a registered trademark / specification of the NMMA.**

Bio-SynXtra™ Marine 2 Cycle Engine Oil contains enhanced lubricity boosters and additional cleanliness chemistry that improves lubrication performance for high output Motorcycle API TC, Husqvarna Chain Saw 242/266 and Meets or Exceeds TC-W3 outboard water-cooled engine requirements. It is specifically formulated to reduce visible smoke and burn clean, minimizing deposits and carbon buildup, and preventing ring sticking and spark plug fouling. In addition, this technology minimizing deposits and carbon buildup in equipment operating at high and low RPMs.

Bio-SynXtra™ Marine 2 Cycle Engine Oil is recommended in both carbureted and Direct Fuel Injected (DFI) systems. This ashless, Low-Smoke Formula contains **Stabilized*** Technology to improve fuel stability.

For premixed fuel-oil systems, see owner's manual for recommended fuel: oil ratio.

Typical Characteristics

Property	Typical Value	Method
Viscosity, cSt 100°C	8.0	ASTM D-445
Flash point, °C	185	ASTM D-93
Pour point, °C	-42	ASTM D-97
TBN (mg KOH/g)	6.0	ASTM D-2896

TC-W3 Program Summary

Bench Tests

		Method Pass/Fail Criteria
Cloud point, °C	-29	ASTM D-2500
Compatibility	clear	NMMA_CTCW homogeneous after mixed separately with each reference oil and stored 48 hours
Brookfield (fluidity) cP @ -25°C Evaluation	5130 Pass	ASTM D-2988 less than 7500 cP
Miscibility (inversions @ -25°C) Candidate/reference Evaluation	50/85 Pass	ASTM D-4682/#992 no more than 10% inversions than reference*
Rust test, % Candidate/reference Evaluation	0/3.6 Pass	NMMA Procedure equal to or better than reference*
Filterability, % Change, Candidate/Evaluation	5.37 Pass	NMMA_FPT Procedure decrease in flow not greater than 20%
Lubricity Test	Pass	AF-27

¹ **Readily Biodegradable >60% within 28 days according to ASTM D 5864**

STABILIZED by Renewable Lubricants is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

2-CYCLE ENGINE OIL PROGRAM SUMMARY

TYPICAL ENGINE TEST RESULTS:

OMC 40 Horsepower Test (100 hours) Average Piston Varnish, Candidate/Reference Top Ring Stick, Candidate/Reference Evaluation		Not lower than 0.6 below same ratings of reference**
OMC 70 Horsepower Test (100 hours) Average Piston Deposits, Candidate/Reference Second Ring Stick, Candidate/Reference Evaluation		Equal to or better than some ratings of reference**
Mercury 15 Horsepower Test (100 hours) Scuffing, Candidate Evaluation Bearing Stickiness, Candidate Evaluation Compression Loss, Candidate Evaluation Overall Candidate Evaluation	100 hours Pass Pass Pass Pass	100 hours with no stuck rings, plus a) scuffing within allowable limits (30%) b) needles must fall easily from wrist pin c) 20 psi maximum compression loss (reference** run every 5 candidate runs)
Yamaha CE50S Tightening/Lubricity Test Torque Drop, lb-in. Candidate/Reference/Eval.	4.16 / 4.26 / Pass	Equal to or better than reference** within 90% confidence level
Yamaha CE50S Preignition Test (100 hours) Major Preignitions, Candidate/Reference/Eval.		Equal to or better than reference**

Reference ** OS250541

<u>Availability</u>	<u>F.O.B.: Hartville, Ohio, USA</u>	<u>Quart</u>	<u>Gallon</u>	<u>Pail</u>	<u>Drum</u>	<u>Totes</u>	<u>Bulk</u>
Product Item #		85201	85203	85204	85206	85207	85207