



## Renewable Lubricants, Inc.

476 Griggy Rd., P.O. Box 474

Hartville, Ohio 44632-0474

Voice: 330.877.9982 Fax 330.877.2266

Web: [www.renewablelube.com](http://www.renewablelube.com)

### Bio-Heavy Duty™ Cutting Oil

**STABILIZED™**  
by Renewable Lubricants

#### *"Biobased Lubricants that Perform Like Synthetics"*

A heavy duty, ultimately biodegradable<sup>1</sup>, vegetable based, cutting oil which provides excellent performance in a wide variety of machining operations on tough ferrous alloys as well as mild steel and cast iron. These operations include: milling, drilling, turning, grinding, light and medium duty broaching, and thread cutting and tapping. This product replaces the use of products that contain chlorinated paraffin additives.

Performance is enhanced by use of the Stabilized HOBS's, natural fatty acid composition, which provides cutting tool wetting and oiliness; combined with sulfur/phosphorous EP and antiwear technology. The super high viscosity index of the Stabilized HOBS adds additional lubrication qualities to this high performance lubricant.

Bio-Heavy Duty™ Cutting Oil is an ENVIRONMENTALLY RESPONSIBLE cutting oil that is formulated from renewable agricultural plant resources. We believe Earth's environmental future rests in the use of renewable materials.

#### Typical Specifications

<u>SAE Grade</u>	<b>30</b>
ISO Grade	46
Pounds/Gallon @ 60°F.	7.39
Specific Gravity @60°F.	0.887
VISCOSITIES:	
@100°C., cSt.	9.63
@40°C., cSt.	45.7
Viscosity Index	202
Flash Point, COC, °C.	250
Pour Point, °C.	-18
Copper Corrosion ASTM D-130	1-B
Rust Prevention ASTM D-665	
A (Distilled Water)	No Rust
B (Synthetic Sea Water)	No Rust
Tapping Test	
304 Stainless Steel, % Efficiency	125
1020 HR Steel, % Efficiency	120
Falex EP Test, (Fail load lbs.)	4250

STABILIZED by Renewable Lubricants\* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

<sup>1</sup> Ultimate Biodegradation (Pw1) within 28 days in ASTM D-5864 Aerobic Aquatic Biodegradation of Lubricants

Patented Product: US Patent 6,383,992, US Patent 6,534,454 with additional Pending and Foreign Patents

\* Trademark of Renewable Lubricants, Inc.  
Copyright 1999 Renewable Lubricants, Inc.

**Availability** **F.O.B. :Hartville, Ohio, USA** **1 Gallon** **5 Gallon Pail** **Drum** **Totes** **Bulk**  
RLI Product Item # 86713 86714 86716 86717 86719