



Renewable Lubricants, Inc.

476 Griggy Rd., P.O. Box 474

Hartville, Ohio 44632-0474

Voice: 330.877.9982 Fax 330.877.2266

Web: www.renewablelube.com

Bio-Food Grade™ General Purpose Lubricant/ Release Agent SAE 20



3H, H1, H2



"Biobased Lubricants that Perform Like Synthetics"

Bio-Food Grade™ General Purpose Lubricant/ Release Agent is a special vegetable oil-based formula (non-petroleum) that contains ingredients which are 'Generally Regarded as Safe' (GRAS) for food applications. This biobased product is acceptable for use as a Release Agent (3H) on grills, ovens, loaf pans, boning benches, chopping boards, canning lids, knife cutting and honing oil, or other hard surfaces in **contact** with meat, fish, and poultry food products to prevent food from adhering during processing. In addition, it performs as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a light general purpose lubricant in applications where there is a very high possibility of the lubricant coming into direct contact with food products. It has excellent oxidative stability and high biodegradability and can be used in environmentally sensitive areas such as in agriculture, marine, and food processing plants.

Bio-Food Grade™ General Purpose is an ENVIRONMENTALLY RESPONSIBLE, biodegradable lubricant that is formulated from renewable agricultural plant resources. We believe Earth's environmental future rests in the use of renewable material.

Applications With Incidental Food Contact In and Around Food Processing Equipment Areas:

Drip oilers, air-oilers, air-tools, water pumps, bearings, machine oil, roller chains, cables, small electric motors bearings, light circulating oil, e., and general lubrication. This product may also be used in light reduction units and low temperature hydraulic systems where original equipment manufacturers require an ISO 32 or 46 R&O Lubricant.

NSF Registration

140449 3H, H1, H2

Typical Specifications

Specific Gravity @60°F.	.91
VISCOSITIES:	
@100°C., cSt. (D-445)	8.5
@40°C., cSt. (D-445)	39.1
Viscosity Index (D-2270)	202
Flash Point, COC (D-92)	328 °C (Safe, very high flash)
Pour Point, °C (D-97)	-18
Copper Corrosion (D-130) 3hr @ 100°C	1A
Acid Number (D-974)	0.10
Foam Sequence I, II, III (D-892) 10 min.	0 Foam
Rust Prevention, (D-665 A)	Pass Clean
4 Ball Wear Scar Diam (mm) (D-4172)	.60
Dielectric Insulating Property (D-877)	47 kV
Biodegradability (D-5864) Pw1	Yes

STABILIZED by Renewable Lubricants* is RLI's trademark on their proprietary and patented technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

¹ This product is acceptable as a Release Agent (3H) in contact with food and as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure and/or direct contact to food.

Proprietary formulation

™ Trademark of Renewable Lubricants, Inc.

Copyright 2011 Renewable Lubricants, Inc.

Availability F.O.B. :Hartville, Ohio, USA

1 Gallon

5 Gallon Pail

Drum

Totes

Bulk

RLI Product Item #

87013

87014

87016

87017

87019