

## **Renewable Lubricants, Inc.**

476 Griggy Rd., P.O. Box 474 Hartville, Ohio 44632-0474 Voice: 330.877.9982 Fax 330.877.2266 Web: www.renewablelube.com

# **RLI E.P. 300 Lithium Multipurpose Grease**

### **NLGI # 2**

#### PRODUCT DESCRIPTION

RLI E.P. 300 Grease is a lithium 12 hydroxy lubricating grease formulated with the highest quality base oils available, and is fortified with rust and oxidation inhibitors as well as extreme pressure additives. This product has been formulated with a special additive package which insures high film strength, extreme pressure (EP) and anti-wear properties.

#### **RECOMMENDED APPLICATIONS**

For use in/on any of the following:

- Plain/rolling-element bearings
  - Compressors
  - Fans
  - Centrifugal pumps
  - Chassis parts
  - U-joints
  - Water pumps on passenger cars
  - Track Rollers
  - Commercial lawn mowers
  - General-purpose/shop/industrial grease
  - Underground mining machinery
  - Crushers
  - Vibrating screens
  - Centralized lubrication systems

#### **PRODUCT BENEFITS**

Has a variety of uses and is formulated with special additive to perform well under extreme pressure.

#### TYPICAL PROPERTIES

Thickener Type Lit	hium
Color An	nber
Texture But	ttery
Appearance Sm	nooth
Operating Temperature Range -30	$^{\circ}$ F to +250 $^{\circ}$ F
Penetration ASTM D 217	
Worked 60 Strokes @ 77 °F 265	5-295
Dropping Point, °F (°C) ASTM D 2265 350	0 (177)
Oil Separation, % Loss Max ASTM D 1742 10	
4 Ball Wear Test, mm Scar Diameter ASTM D 2266 0.4	5
4 Ball E.P. Weld Point, ASTM D 2596 250	0
4 Ball Load Wear Index, Kgf ASTM D 2596 40	
Water Washout, % Loss MaxASTM D 250910	
Timken Load Carrying Test of Grease Lbs. ASTM D 2509 45	
Rust Preventative Properties of Greases ASTM D 1743 Pas	<b>SS</b>
Pressure Vessel Oxidation PSI Drop ASTM D 942 5	
Wheel Bearing Leakage, grams LossASTM D 42905	
Copper Corrosion of Greases ASTM D 4048 1b	
Base Oil Characteristics ASTM D 445	
Viscosity @ 100°C cSt 11.	.5-14.5
Viscosity @ 40°C cSt 150	0-200
Viscosity Index 50	

\* Trademark of Renewable Lubricants, Inc.

Convright	1999	Renewable	Lubricants,	Inc

<u>Availability</u>	F.O.B. :Manufacturer	14 oz. Tube	35 lb Pail	120 lb Keg	400 lb Drum
RLI Product Item #		88921	88924	88925	88926